



 trillium

HD40

**HIGH PERFORMANCE 4-INCH CLASS STABILIZED EO/IR
CAMERA SYSTEM FOR SMALL UNMANNED VEHICLES**



DIRECT DRIVE ARCHITECTURE

Best-in-class robustness and stability



EMBEDDED VIDEO PROCESSING

Electronic stabilization and scene tracking



ONBOARD GPS/INS

Accurate real-time vehicle and target location



DIGITAL RANGEFINDER

Range to target using onboard elevation data



ITAR FREE

Non-controlled configurations available



720P HD DIGITAL VIDEO

Fully digital, h.264-compliant video pipeline



ENVIRONMENTALLY SEALED

Highly resistant to dust and water



VISIBLE AND THERMAL CMERAS

Day and day/night operations with a single payload



ETHERNET INTERFACE

Video and gimbal control over ethernet or RS-232



METADATA

Target location, gimbal health, and more

SOFTWARE

FEATURES

- Onboard h.264 compression with adjustable bitrate
- Dynamic or static IP addressing
- Field upgradable software
- Onboard electronic stabilization
- Onboard scene tracking
- MISB-compliant output including embedded KLV metadata
- Optional target tracking with external module

GPS/INS

- IMU co-located with cameras
- 1.5° (typical) total system accuracy
- Real time geointing and geolocation
- Attitude, velocity and position computed at 200Hz
- Onboard GPS receiver
- GPS and heading accepted over serial or Ethernet
- Dual GPS heading support

ELECTRICAL

- Control over Ethernet or serial
- Ethernet and analog video
- 15W average, 75W peak power consumption
- 24VDC regulated input, external regulation accepting 10V to 30V available

- Interface connector: 37 pin Nano Bi-Lobe connector conforming to MIL-DTL-32139
- GPS connector: MMCX
- Analog video connector: MMCX
- GPS antenna: 3.3V active, L1 band

MECHANICAL

SPECS

- Machined magnesium housing
- Glass and Germanium windows
- Direct drive brushless motors
- 0.02° encoder resolution
- 60Hz closed loop stabilization bandwidth
- 50µRAD - 150µRAD RMS jitter



HD40-LV

CAMERA CONFIGURATIONS

CONFIGURATION	WEIGHT	CAMERAS	FOV
HD40-XV	860g	Visible Global Shutter 30X	59.2°-1.8°
HD40-LV	670g	Visible Global Shutter 10X LWIR 640 with 24mm lens	54°-4.9° 18.2°